Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources		-AITON (LO) 2019/2		
Supplier's name	or trade mark:	Tracon Electric		
Supplier's addre	ess: Customer se	rvice, Pallag 23, 212	20 Dunakeszi Pest, HU	
Model identifie	r: LHDK18NW			
Type of light so	urce:			
Lighting technol	ogy used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)		Meghajtó		
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para		I
Parameter		Value	Parameter	Value
		General product p		I
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		18	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 440 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		18,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	210	Spectral power dis-	See image
sions without separate con- trol gear, light- ing control	Width Depth	210 50	tribution in the range 250 nm to 800 nm, at full-load	in last page

parts and non- lighting con- trol parts, if any (millime-						
tre) Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,400 0,400			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	8	Survival factor	1,00			
the lumen maintenance factor	0,70					
Parameters for LED and OLED m	ains light sources:	-				
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-': not applicable; (b)'-': not applicable;

