Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources	LLLOAILD KLOOI	-A11014 (E0) 2019/2	2015 with regard to ener	gy labelling of light	
Supplier's name	e or trade mark:	Tracon Electric			
Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU					
Model identifie	r: FILGG958W				
Type of light so	urce:				
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS	
Light source cap-type		E27			
(or other electric interface)					
Mains or non-m	nains:	MLS	Connected light source (CLS):	No	
Colour-tuneable	e light source:	No	Envelope:	-	
High luminance light source:		No			
Anti-glare shield:		No	Dimmable:	No	
		Product para		T -	
Parameter		Value	Parameter	Value	
		General product p	<u> </u>	T _	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		7	Energy efficiency class	F	
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	2 500	
On-mode power (P _{on}), expressed in W		7,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82	
Outer dimen-	Height	95	Spectral power dis-	See image	
sions without separate con- trol gear, light- ing control	Width Depth	95 145	tribution in the range 250 nm to 800 nm, at full-load	in last page	

parts and non- lighting con- trol parts, if any (millime-						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)	0,400 0,390			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9	Survival factor	1,00			
the lumen maintenance factor	0,70					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-': not applicable; (b)'-': not applicable;

