## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

## Supplier's name or trade mark: Tracon Electric

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-SZH-72-CW

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	Meghajtó				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					

	Value	Parameter	Value		
General product parameters:					
nption in on- 00 h), rounded st integer	36	Energy efficiency class	F		
s flux (φuse), in- ers to the flux in , in a wide cone rrow cone (90º)	3 600 in Wide cone (120°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	6 000		
ver (P <sub>on</sub> ), ex-	36,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Height	5 000	Spectral power dis-	See image		
Width Depth	8	tribution in the range 250 nm to 800 nm, at full-load	in last page		
	00 h), rounded st integer s flux (¢use), in- ers to the flux in , in a wide cone rrow cone (90º) ver (Pon), ex- candby power expressed in W the second dec- Height Width	General product pnption in on- 00 h), rounded st integer3600 h), rounded st integer3 600 in Wide cone (120°)a wide cone rrow cone (90°)3 600 in Wide cone (120°)ver (Pon), ex- expressed in W the second dec-36,0Height5 000Width8	General product parameters:Inption in on- 00 h), rounded st integer36Energy efficiency classS flux (\$\phiuse\$), in- ers to the flux in , in a wide cone rrow cone (90°)3 600 in Wide cone (120°)Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be setver (P_on), ex- expressed in W the second dec-36,0Standby power (P_{sb}), expressed in W and rounded to the sec- ond decimalandby power expressed in W the second decColour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be setHeight5 000Spectral power dis- tribution in the range 250 nm to 800		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,400		
		nates (x and y)	0,400		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	9	Survival factor	1,00		
the lumen maintenance factor	0,70				

(a)'-' : not applicable;

(b)<sub>'-'</sub> : not applicable;

