## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-SZH-72-NW

_	•		
Typa	Λt	liaht	source:
IVDE	VI.	IIKIIL	source.

General product parameters:					
Parameter	Value	Parameter	Value		
Product parameters					
Anti-glare shield:	No	Dimmable:	Yes		
High luminance light source:	No				
Colour-tuneable light source:	No	Envelope:	-		
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Light source cap-type (or other electric interface)	Meghajtó				
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Type of light source.					

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
<u> </u>	nption in on- 00 h), rounded st integer	36	Energy efficiency class	F		
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		3 600 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P <sub>on</sub> ), expressed in W		36,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimensions without separate control gear, lighting control	Height	5 000	Spectral power dis-	See image		
	Width	8	tribution in the	in last page		
	Depth	2	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,400		
		nates (x and y)	0,400		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	9	Survival factor	1,00		
the lumen maintenance factor	0,70				

(a)'-': not applicable; (b)'-': not applicable;

