Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	Tracon Ele	ctric
--------------------------------	------------	-------

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-SZKH-144-NW

_	•			
Type	Λt	light	COLL	rco.
IVDE	VI.	HEILL	3UU	ıce.

ing control

				<u> </u>
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS
Light source cap	o-type	Meghajtó		
(or other electri	c interface)			
Mains or non-m	ains:	NMLS	Connected light source (CLS):	No
Colour-tuneable	e light source:	No	Envelope:	-
High luminance	light source:	No		
Anti-glare shield	d:	No	Dimmable:	Yes
		Product para	meters	
Parameter		Value	Parameter	Value
		General product p	arameters:	
Energy consur mode (kWh/10 up to the neare	00 h), rounded	72	Energy efficiency class	F
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide coneerrow cone (90º)	7 200 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode pow pressed in W	ver (P _{on}), ex-	72,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
(P _{net}) for CLS, 6	andby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	5 000	Spectral power dis-	See image
sions without	Width	10	tribution in the	in last page
separate con- trol gear, light-	Depth	2	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,400
		nates (x and y)	0,400
Parameters for LED and OLED light sources:			
R9 colour rendering index value	9	Survival factor	1,00
the lumen maintenance factor	0,70		

(a)'-': not applicable; (b)'-': not applicable;

