Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources	ELLO/ (I LD I ILCO)	27111011 (20) 2013/2	.013 With regard to energ	By labelling of light			
Supplier's name or trade mark: Tracon Electric Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU							
							Model identifier: SMDMR165CW
Type of light so	urce:						
Lighting technology used:		LED	Non-directional or directional:	NDLS			
Light source cap-type (or other electric interface)		MR16					
Mains or non-mains:		NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:		No	Envelope:	-			
High luminance light source:		No					
Anti-glare shield:		No	Dimmable:	No			
		Product para		T -			
Parameter		Value	Parameter	Value			
		General product p	<u></u>	I			
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		5	Energy efficiency class	G			
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		300 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500			
On-mode power (P _{on}), ex- pressed in W		5,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00			
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82			
Outer dimen-	Height	50	Spectral power dis-	See image			
sions without separate con- trol gear, light- ing control	Width Depth	50 55	tribution in the range 250 nm to 800 nm, at full-load	in last page			

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,400			
		nates (x and y)	0,390			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9	Survival factor	1,00			
the lumen maintenance factor	0,70					

(a)'-': not applicable; (b)'-': not applicable;

