Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

| sources | LLLOAILD KLOOI | -AHON (EU) 2019/2 | 2015 with regard to ener | gy labelling of light | |
|--|------------------|----------------------------|--|-----------------------|--|
| Supplier's name | e or trade mark: | Tracon Electric | | | |
| Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU | | | | | |
| Model identifie | r: SMDGU107W | | | | |
| Type of light so | urce: | | | | |
| Lighting techno | logy used: | LED | Non-directional or directional: | NDLS | |
| Light source cap-type | | GU10 | | | |
| (or other electric interface) | | | | | |
| Mains or non-m | nains: | MLS | Connected light source (CLS): | No | |
| Colour-tuneable | e light source: | No | Envelope: | - | |
| High luminance light source: | | No | | | |
| Anti-glare shield: | | No | Dimmable: | No | |
| | | Product para | | T . | |
| Parameter | | Value | Parameter | Value | |
| | | General product | <u>-</u> | | |
| Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer | | 7 | Energy efficiency class | G | |
| Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°) | | 450 in Wide cone (120°) | Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set | 2 700 | |
| On-mode power (P _{on}), expressed in W | | 7,0 | Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal | 0,00 | |
| Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal | | - | Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set | 82 | |
| Outer dimen- | Height | 50 | Spectral power dis- | See image | |
| sions without separate con- trol gear, light- ing control | Width Depth | 50 55 | tribution in the range 250 nm to 800 nm, at full-load | in last page | |

| parts and non- lighting con- trol parts, if any (millime- | | | | | | |
|---|------|--|-------|--|--|--|
| tre) | | | | | | |
| Claim of equivalent power ^(a) | - | If yes, equivalent power (W) | - | | | |
| | | Chromaticity coordi- | 0,380 | | | |
| | | nates (x and y) | 0,400 | | | |
| Parameters for LED and OLED light sources: | | | | | | |
| R9 colour rendering index value | 9 | Survival factor | 1,00 | | | |
| the lumen maintenance factor | 0,70 | | | | | |
| Parameters for LED and OLED mains light sources: | | | | | | |
| displacement factor (cos φ1) | 0,55 | Colour consistency in McAdam ellipses | 6 | | | |
| Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage. | _(b) | If yes then replace- ment claim (W) | - | | | |
| Flicker metric (Pst LM) | 0,0 | Stroboscopic effect metric (SVM) | 0,0 | | | |

(a)'-': not applicable; (b)'-': not applicable;

