Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name or	trade mark:	Tracon Electric
------------	---------	-------------	-----------------

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LBV10WW

T۱	/pe	of	lig	ht	SO	urc	e:
•)	, PC	0.	יסיי		30	u. c	C .

LED	Non-directional or directional:	NDLS
H05VV-F		
2×0,75 mm2		
MLS	Connected light source (CLS):	No
No	Envelope:	-
No		
No	Dimmable:	No
	H05VV-F 2×0,75 mm2 MLS No	directional: H05VV-F 2×0,75 mm2 MLS Connected light source (CLS): No Envelope: No

Product parameters

Product parameters					
Parameter		Value	Parameter	Value	
	General product parameters:				
	mption in on- 00 h), rounded st integer	10	Energy efficiency class	G	
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	3 000	
On-mode power (P _{on}), expressed in W		10,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82	
Outer dimen-	Height	600	Spectral power dis-	See image	
sions without	Width	22	tribution in the	in last page	
separate con- trol gear, light- ing control	Depth	35	range 250 nm to 800 nm, at full-load		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,390 0,400		
Parameters for LED and OLED lig	Parameters for LED and OLED light sources:				
R9 colour rendering index value	9	Survival factor	1,00		
the lumen maintenance factor	0,70				
Parameters for LED and OLED mains light sources:					
displacement factor (cos φ1)	0,70	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4		

(a)'-': not applicable; (b)'-': not applicable;

