Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			io 13 With regard to effect	8, 8 c8		
Supplier's name	e or trade mark:	Tracon Electric				
Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU Model identifier: LT8GH609CW						
Lighting techno	logy used:	LED	Non-directional or directional:	NDLS		
Light source cap-type		G13				
(or other electric interface)						
Mains or non-m	nains:	MLS	Connected light source (CLS):	No		
Colour-tuneable light source:		No	Envelope:	-		
High luminance light source:		No				
Anti-glare shield:		No .	Dimmable:	No		
		Product para		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
Parameter		Value	Parameter	Value		
Enormy consur	mntion in on	General product p		D		
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		9	Energy efficiency class	D		
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		1 220 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 500		
On-mode power (P _{on}), ex- pressed in W		9,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82		
Outer dimen-	Height	600	Spectral power dis-	See image		
sions without separate con- trol gear, light- ing control	Width Depth	30 30	tribution in the range 250 nm to 800 nm, at full-load	in last page		

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-		
		Chromaticity coordinates (x and y)	0,400 0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	8	Survival factor	1,00		
the lumen maintenance factor	0,70				
Parameters for LED and OLED m	ains light sources:				
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6		
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-		
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0		

(a)'-': not applicable; (b)'-': not applicable;

