Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

sources			.013 With regard to energ	8) iace8 org
Supplier's name	e or trade mark:	Tracon Electric		
Supplier's addre	ess: Customer se	rvice, Pallag 23, 21	20 Dunakeszi Pest, HU	
Model identifie	r: LFV60NW			
Type of light so	urce:			
Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		Meghajtó		
(or other electric interface)				
Mains or non-mains:		MLS	Connected light source (CLS):	No
Colour-tuneable light source:		No	Envelope:	-
High luminance light source:		No		
Anti-glare shield:		No	Dimmable:	No
		Product para	T	1
Parameter		Value	Parameter	Value
		General product p	T	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		60	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		4 200 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		60,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	82
Outer dimen-	Height	320	Spectral power dis-	See image
sions without separate con- trol gear, light- ing control	Width Depth	320 89	tribution in the range 250 nm to 800 nm, at full-load	in last page

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,400
		nates (x and y)	0,400
Parameters for LED and OLED lig	ht sources:		
R9 colour rendering index value	9	Survival factor	1,00
the lumen maintenance factor	0,70		
Parameters for LED and OLED m	ains light sources:		
displacement factor (cos φ1)	0,90	Colour consistency in McAdam ellipses	6
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-
Flicker metric (Pst LM)	1,0	Stroboscopic effect metric (SVM)	0,4

(a)'-': not applicable; (b)'-': not applicable;

