Product Information Sheet

ing

control

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light

sources			o 13 With regard to energ	5, 1425 6							
Supplier's name or trade mark: Tracon Electric Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU Model identifier: LED-DLS-6NW											
							Type of light so	urce:			
							Lighting technology used:		LED	Non-directional or directional:	NDLS
Light source cap-type		Meghajtó									
(or other electric interface)											
Mains or non-mains:		MLS	Connected light source (CLS):	No							
Colour-tuneable light source:		No	Envelope:	-							
High luminance light source:		No									
Anti-glare shield:		No	Dimmable:	No							
		Product para	meters								
Parameter		Value	Parameter	Value							
		General product p	parameters:								
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer		6	Energy efficiency class	G							
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		480 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000							
On-mode power (P _{on}), expressed in W		6,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00							
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82							
Outer dimen-	Height	120	Spectral power dis-	See image							
sions without separate con- trol gear, light-	Width Depth	120 25	tribution in the range 250 nm to 800 nm, at full-load	in last page							

norts and non	1		1			
parts and non-						
lighting con-						
trol parts, if						
any (millime-						
tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent	-			
		power (W)				
		Chromaticity coordi-	0,390			
		nates (x and y)	0,390			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9	Survival factor	1,00			
the lumen maintenance factor	0,70					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	0,50	Colour consistency	6			
		in McAdam ellipses				
Claims that an LED light source	_(b)	If yes then replace-	-			
replaces a fluorescent light		ment claim (W)				
source without integrated bal-		, ,				
last of a particular wattage.						
Flicker metric (Pst LM)	1,0	Stroboscopic effect	0,4			
I HEREI HIEUTE (FSt LIVI)	1,0	metric (SVM)	0,4			

(a)'-': not applicable; (b)'-': not applicable;

