Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name or	trade mark:	Tracon Electric
------------	---------	-------------	-----------------

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-DLNIP-6NW

Type of light source	Type	of light	source:
----------------------	------	----------	---------

Lighting technology used:	LED	Non-directional or	NDLS
		directional:	
Light source cap-type	Meghajtó		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light	No
		source (CLS):	
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

Product parameters

Froduct parameters				
Parameter		Value	Parameter	Value
General product parameters:				
	mption in on- 00 h), rounded st integer	6	Energy efficiency class	G
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)		450 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W		6,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
Networked standby power (P _{net}) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82
Outer dimen-	Height	75	Spectral power dis-	See image
sions without	Width	75	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	20	range 250 nm to 800 nm, at full-load	

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-	
			Chromaticity coordinates (x and y)	0,370 0,390	
Parameters for	Parameters for LED and OLED light sources:				
R9 colour rende	ring index value	10	Survival factor	1,00	
the lumen maintenance factor		0,70			
Parameters for LED and OLED mains light sources:					
displacement fa	ctor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6	
Claims that an L replaces a flu source without last of a particul	orescent light integrated bal-	_(b)	If yes then replace- ment claim (W)	-	
Flicker metric (P	st LM)	0,0	Stroboscopic effect metric (SVM)	0,0	

(a)'-': not applicable; (b)'-': not applicable;

