## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-DLNS-9NW

Tν	pe	of	light	source	:
٠,	<b>P</b> C	٠.		504.00	••

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Meghajtó		
(or other electric interface)			
Mains or non-mains:	MLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

## **Product parameters**

Product parameters						
Parameter		Value	Parameter	Value		
General product parameters:						
Energy consur mode (kWh/10 up to the neare	00 h), rounded	9	Energy efficiency class	G		
dicating if it refe a sphere (360º)	s flux (фuse), ineers to the flux in, in a wide cone arrow cone (90º)	720 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000		
On-mode power (P <sub>on</sub> ), expressed in W		9,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82		
Outer dimen-	Height	150	Spectral power dis-	See image		
sions without	Width	150	tribution in the	in last page		
separate con- trol gear, light- ing control	Depth	25	range 250 nm to 800 nm, at full-load			

parts and non- lighting con- trol parts, if any (millime-						
tre)						
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,390			
		nates (x and y)	0,390			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	11	Survival factor	1,00			
the lumen maintenance factor	0,70					
Parameters for LED and OLED m	ains light sources:					
displacement factor (cos φ1)	0,50	Colour consistency in McAdam ellipses	6			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replace- ment claim (W)	-			
Flicker metric (Pst LM)	0,0	Stroboscopic effect metric (SVM)	0,0			

(a)'-': not applicable; (b)'-': not applicable;

