## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier	's name or	trade marl	<b>k:</b> Tracon l	Electric
Supplier	's name or	trade mari	<b>k:</b> Tracon	Electric

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-SZK-48-NW

Type of light sou
-------------------

Lighting technology used:	LED	Non-directional o directional:	r NDLS	
Light source cap-type	Meghajtó			
(or other electric interface)				
Mains or non-mains:	NMLS	Connected ligh source (CLS):	t No	
Colour-tuneable light source:	No	Envelope:	-	
High luminance light source:	No			
Anti-glare shield:	No	Dimmable:	Yes	
Product parameters				
Parameter	Value	Parameter	Value	

Product parameters					
Parameter		Value	Parameter	Value	
General product parameters:					
<u> </u>	nption in on- 00 h), rounded st integer	24	Energy efficiency class	G	
dicating if it refe a sphere (360º)	s flux (фuse), in- ers to the flux in , in a wide cone errow cone (90º)	900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000	
On-mode power (P <sub>on</sub> ), ex- pressed in W		24,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00	
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal		-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	82	
Outer dimen-	Height	5 000	Spectral power dis-	See image	
sions without separate con- trol gear, light- ing control	Width	8	tribution in the range 250 nm to 800 nm, at full-load	in last page	
	Depth	4			

parts and non- lighting con- trol parts, if any (millime- tre)					
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-		
		Chromaticity coordi-	0,380		
		nates (x and y)	0,380		
Parameters for LED and OLED light sources:					
R9 colour rendering index value	9	Survival factor	1,00		
the lumen maintenance factor	0,70				

(a)'-': not applicable; (b)'-': not applicable;

