Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's	name or	trade mark:	Tracon Electric
------------	---------	-------------	-----------------

Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU

Model identifier: LED-SZK-96-WW

_	•			
Tyna	At.	liaht	source	٥.
IVDC	OI.	IIGIIL	Souic	឴

On-mode power

Networked standby

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

pressed in W

imal

 $(P_{on}),$

power

Lighting technology used:	LED	Non-directional or	NDLS
Light according	NA : + - 4	directional:	
Light source cap-type	Meghajtó		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product para	meters	
Parameter	Value	Parameter	Value
	General product	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	48	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	1 800 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to	3 000

the nearest 100 K, that can be set

Standby power (P_{sb}),

expressed in W and rounded to the sec-

Colour rendering in-

dex, rounded to the

ond decimal

			ues that can be set	
Outer dimen-	Height	5 000	Spectral power dis-	See image
sions without	Width	8	tribution in the	in last page
separate con- trol gear, light- ing control	Depth	4	range 250 nm to 800 nm, at full-load	

48,0

0,00

82

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,390
		nates (x and y)	0,380
Parameters for LED and OLED light sources:			
R9 colour rendering index value	9	Survival factor	1,00
the lumen maintenance factor	0,70		

(a)'-': not applicable; (b)'-': not applicable;

