Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: Tracon Electric						
Supplier's address: Customer service, Pallag 23, 2120 Dunakeszi Pest, HU						

Model identifier: LED-SZ-48-NW

_	•			
Tyna	Ot.	lioht	sour	CD.
IVDC	O.	IIGIIL	30ui	LC.

Networked standby

imal

ing

Outer dimen-

sions without

separate con-

trol gear, light-

control

(P_{net}) for CLS, expressed in W

and rounded to the second dec-

Height

Width

Depth

power

<i>7</i> . 0			
Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	Meghajtó		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes
	Product para	meters	
Parameter	Value	Parameter	Value
	General product p	parameters:	
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	24	Energy efficiency class	G
Useful luminous flux (φuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	900 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000
On-mode power (P _{on}), expressed in W	24,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
		+	

5 000

8

3

Colour rendering in-

dex, rounded to the

nearest integer, or the range of CRI-val-

ues that can be set

tribution

Spectral power dis-

range 250 nm to 800

nm, at full-load

in

82

See image

in last page

parts and non- lighting con- trol parts, if any (millime- tre)						
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,400			
		nates (x and y)	0,380			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	8	Survival factor	1,00			
the lumen maintenance factor	0,70					

(a)'-': not applicable; (b)'-': not applicable;

